

E195BV-SHDC 19" LED TV



Specification

Display	
Active Screen Size	18.5" Diagonal Viewable
Native Resolution	1366 x 768
Refresh Rate	Up to 60Hz Refresh Rate
Aspect Ratio	16:9
Response Time	5ms (G-to-G)
Dynamic Contrast Ratio	1,000,000:1
Color Depth	16.7M
Contrast Ratio	1,000:1
Brightness (Typ.)	250 cd/m²
Viewing Angle	Vertical: 160° / Horizontal: 170°
Backlight Life	30,000+ hours
Features	
On Screen Display Control (OSD)	Picture, Sound, Channel, Setup
Color Temperature	Warm, Normal, Cool, Standards
Adjustable Picture Control*	Brightness, Contrast, Backlight, Color, Tint, Sharp
Picture Presets	Normal, Wide, Cinema, Zoom

SCEPTRE®		
Built-in Tuner	ATSC / NTSC / Clear QAM	
OSD Supported Languages	English (Default), Spanish, French, Chinese	
Weak Signal Enhancement	Yes	
Comb Filter	3D	
De-interlace Technology	3D	
Auto Dynamic Contrast Mode	Yes	
Noise Reduction	Yes	
MPEG Noise Reduction	Yes	
Surround Sound Mode	Yes	
Sound Equalizer Settings	Yes (7-band)	
Auto Volume Level Control	Yes	
Wall Mountable	Yes	
Neck & Base Detachable	Yes	
Energy Guide	5.3	
Audio Features		
Speakers	2 x 3W/4Ω	
Video Features		
White Balance	Available	
Outputs		
Headphone Output	1 x Earphone terminal (black)	
Inputs		
PC Audio In	1 x Audio In terminal (black)	
Inputs & amp; Outputs		
HDMI (# of Ports & Version)	2 x HDMI	
Supported HDMI Signals	1080/24p, 1080/60p, 1080i, 720p, 480p, 480i	
Cable / Antenna Input	1 x IEC-Connector 75 Ohms	
Supported HDTV Signals	1080p, 1080i, 720p, 480p, 480i	
SPDIF Audio Output	1 x (SPDIF, Coaxial, Orange)	
VGA (# of Ports)	1 x D-SUB terminal (blue, 15 pin)	
Component (YPbPr) Input	1 x Component (Audio input shared with composite)	
USB	1 x USB 2.0 Slot	
Composite Video	1 x Composite	
HDTV Signal Compatibility		
VGA Input Support	1360 x 768 @ 60 Hz (Native & Max)1280 x 768 @ 60 Hz1024 x 768 @ 60 Hz800 x 600 @	
	60 Hz	
Mechanical Features		
VESA Mount Pattern (mm)	100 x 100	
VESA Mount Screw Size (mm)	M4 x 8mm	
Dimensions		
With Stand (inches, W x H x D)	17.88 x 12.81 x 6.06	
Without Stand (Inches, W x H x D)	17.88 x 11.13 x 1.93	
Carton Box Dimension (inches, W x H x D)21.1 x 15.7 x 4.6		


SCEPTRE®		
Weight		
Net Weight with Stand (lbs)	5.73 lbs	
Net Weight without Stand (lbs)	5.29 lbs	
Gross Weight (lbs)	10.6 lbs	
Power		
Power Range (V, A, Hz)	100 - 240V 60 Hz	
Power Consumption (Typical)	30W (Max)24W (Typ.)≤0.5 W (Min)	
Regulations / Certifications		
Certificates	cTUVus, FCC, Energy Star	
Warranty		
Limited Parts and Labor	One Year Limited Parts and Labor	
What's in the Box?		
Remote Control Model No	<a< th=""></a<>	

href="https://www.sceptre.com/Accessories/Remote-Control/TV-Remote-Control-142021"

270010C-product745category19category69.html">142021270010C



Key Features





LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.

HDMI

HDMI not only delivers superior digital video and audio, but also, connects both to the TV with only one cable.

Coaxial Digital Out

Offering superior backwards compatibility for stereo receivers. This Sceptre TV is equipped with a Coaxial Digial audio output which will enrich your TV audio experience with the coaxial supported soundbar, soundbase or audio equipment.







USB

Let's you view your pictures as a slideshow or listen to your favorite music via the USB port. Just insert your flash drive into the USB port for the ultimate entertainment.

DTS SRS TruSurround HD

DTS SRS TruSurround HD delivers an enveloping combination of smooth treble and maximum bass response. The broad sound capability produces dialog that is crisp and audible.

Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.



Key Features



30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.