

E205W-16003RTT 20" LED Monitor



Specification


Display

Active Screen Size19.5" Diagonal ViewablePanel TypeTN (Twisted Nematic)Native Resolution1600 x 900 HD+ ResolutionRefresh RateUp to 75Hz Refresh RateAspect Ratio16:9Response Time3ms (G-to-G)Pixel Pitch0.2712mm (H) x 0.2626 mm (V)Dynamic Contrast Ratio1,000,000: 1Color Gamut99% sRGBColor Depth16.7MContrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°Backlight TypeEdge_lit LED	Display	
Native Resolution1600 x 900 HD+ ResolutionRefresh RateUp to 75Hz Refresh RateAspect Ratio16:9Response Time3ms (G-to-G)Pixel Pitch0.2712mm (H) x 0.2626 mm (V)Dynamic Contrast Ratio1,000,000: 1Color Gamut99% sRGBColor Depth16.7MContrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Active Screen Size	19.5" Diagonal Viewable
Refresh RateUp to 75Hz Refresh RateAspect Ratio16:9Response Time3ms (G-to-G)Pixel Pitch0.2712mm (H) x 0.2626 mm (V)Dynamic Contrast Ratio1,000,000: 1Color Gamut99% sRGBColor Depth16.7MContrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Panel Type	TN (Twisted Nematic)
Aspect Ratio16:9Response Time3ms (G-to-G)Pixel Pitch0.2712mm (H) x 0.2626 mm (V)Dynamic Contrast Ratio1,000,000: 1Color Gamut99% sRGBColor Depth16.7MContrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Native Resolution	1600 x 900 HD+ Resolution
Response Time3ms (G-to-G)Pixel Pitch0.2712mm (H) x 0.2626 mm (V)Dynamic Contrast Ratio1,000,000: 1Color Gamut99% sRGBColor Depth16.7MContrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Refresh Rate	Up to 75Hz Refresh Rate
Pixel Pitch0.2712mm (H) x 0.2626 mm (V)Dynamic Contrast Ratio1,000,000: 1Color Gamut99% sRGBColor Depth16.7MContrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Aspect Ratio	16:9
Dynamic Contrast Ratio1,000,000: 1Color Gamut99% sRGBColor Depth16.7MContrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Response Time	3ms (G-to-G)
Color Gamut99% sRGBColor Depth16.7MContrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Pixel Pitch	0.2712mm (H) x 0.2626 mm (V)
Color Depth16.7MContrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Dynamic Contrast Ratio	1,000,000: 1
Contrast Ratio3,000: 1Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Color Gamut	99% sRGB
Brightness (Typ.)250 cd/m²Viewing AngleVertical: 160° / Horizontal: 170°	Color Depth	16.7M
Viewing Angle Vertical: 160° / Horizontal: 170°	Contrast Ratio	3,000: 1
	Brightness (Typ.)	250 cd/m ²
Backlight Type Edge-lit LED	Viewing Angle	Vertical: 160° / Horizontal: 170°
	Backlight Type	Edge-lit LED
Backlight Life 30,000+ Hours	Backlight Life	30,000+ Hours
Anti-Flicker Yes	Anti-Flicker	Yes

Surface TreatmentAnti-glare, Hard Coating (3H)FeaturesOn Screen Display Control (OSD)Quick Start, Picture, Color, SystemColor TemperatureWarm, Normal (Default), Cod, UserPicture PresetsStandard, User, Movie, Eco, FPS, RTSGame PresetsFPS and RTSSDS Supported LanguagesEnglish (Default), French, Spanish, ChineseType of SyncAdaptive SyncBlue Light ShftAvailableAuto Dynamic Contrast ModeAvailableGammaAdjustableAuto Dynamic Contrast ModeAvailableGammaAdjustableAuto Dynamic Contrast ModeAvailableGammaAdjustableAuto Dynamic Contrast ModeAvailableGammaAdjustableAuto Dynamic Contrast ModeAvailableSpacers2 X 2W/4DInputs Sampi OutputsSimm Min-Jack Nardio OutSupported HOMI SignalsUp to 1600 x 900 gr 37Hz: 1080/600, 1080/601, 720p.576j.576i.480p.4801SystemUp to 1600 x 900 gr 37Hz: 1080/601, 720p.576p.576i.480p.4801Vefa (# of Ports)1 x VGA, outo DutSimm Min-Jack Audio OutSignantSupported VGA SignalsUp to 1600 x 900 gr 37Hz: 1080/601, 720p.576p.576i.480p.4801Vefa (# of Ports)1 x VGA, outo DutSimm Min-Jack Audio OutSignalSupported VGA SignalsUp to 3600 x 900 gr 37Hz: 1080/601, 720p.576p.576i.480p.4801Vefa (# of Ports)1 x VGA, outo DutSimm Min-Jack Audio OutSignalSupported VGA SignalsUp to 3600 x 900 gr 37Hz: 1080/601,	SCEPTRE®	
On Screen Display Control (OSD)Quick Start, Picture, Color, SystemColor TemperatureWarm, Normal (Default), Cool, UserPicture PresetsStandard, User, Movie, Eco, PFS, RTSGame PresetsEnglish (Default), French, Spanish. ChineseType of SyncAdaptive SyncBlue Light ShiftAvailableAudo Dynamic Contrast ModeAvailableGammaAdjustableAudo Dynamic Contrast ModeAvailableAudo Dynamic Contrast ModeAvailableGammaAdjustableAudo Prestarces2 x 2W/4QInputs Samp: OutputsI x HDM, 1.3 versionSupported HDMI SignalsUp to 1600 x 900 og 75Hz; 1080/600, 1080/601, 720p.576j.480p.48013.5mm Auxillary Input Jack3.5mm Mini-Jack Audo OutSupported VGA SignalsUp to 1600 x 900 og 75Hz; 1080/600, 1080/601, 720p.576j.480p.48014.64 of Ports)1 x VGA. Output3.5mm Mini-Jack Audo OutSupported VGA SignalsUp to 1600 x 900 og 75Hz; 1080/600, 1080/601, 720p.576j.480p.4801Mechanical FeaturesChasis ColorsBackBackTiltBackward; 15" Forward; 5"Bezel Width0.46"Neck / Stand DetachableYesVESA Mount Screw Size Kounnity MM4 x 10mm (Dpcs)Nortor Nack Hight (Inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18	Surface Treatment	Anti-glare, Hard Coating (3H)
Color TemperatureWarm, Normal (Default), Cool, UserPicture PresetsStandard, User, Movie, Eco, FPS, RTSGame PresetsFPS and RTSOSD Supported LanguagesEnglish (Default), French, Spanish , ChineseType of SyncAdaptive SyncBlue Light ShitAvailableAuto Dynamic Contrast ModeAvailableGammaAdjustableAuto Dynamic Contrast ModeAvailableAuto Default Signals2 x 2W/40Inputs & Bancy OutputsStamm Mini-Jack Nation (Standard)Supported HDMI SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i3.5mm Auxiliary Input Jack3.5mm Mini-Jack Audio OutSupported VGA SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480iMechanical Features	Features	
Picture PresetsStandard, User, Movie, Eco, FPS, RTSGame PresetsFPS and RTSOSD Supported LanguagesEnglish (Default), French, Spanish , ChineseType of SyncAdaptive SyncBlue Light ShiftAvailableAuto Dynamic Contrast ModeAvailableGammaAdjustableAuto FosturosZ x 2W4QInputs Samp. OutputsHDM (or of horts & Version)1 x HDMI, 1.3 versionSupported HDM SignalsU pto 1660 x 900 @ 75Hz: 1080/60p, 1080/60p, 720p,576p,576i,480p,480i3.5mm Auxiliary Input Jack3.5mm Mini-Jack for VGAVGA (or of Ports)1 x VGA, D-sub 15 pin3.5mm Auxiliary Input Jack3.5mm Mini-Jack Audio OutSupported HDM SignalsU pto 1600 x 900 @ 75Hz: 1080/60p, 1080/60p, 720p,576p,576i,480p,480iMechanical FeaturesVersChassis ColorsBlackTitBackward: 15° Forward: 5°Bezel Width0.46°Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Screw Size (Num)M x 10mm (12pcs)Monitor Neck Height (Inches)3.15°SecuritySecurity LockDimensionsUithout 3.01°x 11.35* x 7.02°With Stand (Inches, W x H x D)18.01°x 11.35* x 7.02°Without Stand (Inches, W x H x D)18.01°x 11.28* x 4.06°Stand Separation Dimension (Inches, W x H x D)18.01°x 11.28* x 4.06°Stand Separation Dimension (Inches, W x H x D)18.01°x 11.28* x 4.06°Stand Separation Dimension (Inches, W x H x D)18.01°x 11.28* x 4.06°<	On Screen Display Control (OSD)	Quick Start, Picture, Color, System
Game PresetsFPS and RTSOSD Supported LanguagesEnglish (Default), French, Spanish , ChineseType of SyncAdaptive SyncBlue Light ShiftAvailableAuto Dynamic Contrast ModeAvailableAuto Dynamic Contrast Mode1 x HDMI, 1.3 versionSupported HDMI SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480iSim Headphone Jack (Output)3.5mm Mini-Jack Audio OutSupported VGA SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480iMechanical FeaturesChasis ColorsBlackTiltBackward: 15* Forward: 5*Bezel Width0.46*Neck / Stand DetachableYesVESA Mount Stere Size (m)M 4 x 10mmNeck Screw Size & Quantity (mm)M 4 x 10mmNeck Screw Size & Quantity (mm)M 4 x 10mmNeck Stand Unches, W x H x D)18.01* x 13.58* x 7.02*With Stand (inches, W x H x D)18.01* x 13.58* x 7.02*<	Color Temperature	Warm, Normal (Default), Cool, User
OSD Supported LanguagesEnglish (Default), French, Spanish , ChineseType of SyncAdaptive SyncBlue Light ShiftAvailableAuto Dynanic Contrast ModeAvailableGammaAdjustableAuto Dynanic Contrast ModeAvailableAuto Dynanic Contrast ModeX VM/40Inputs Samp: OutputsVM (# of Ports V Version)Supported HDMI SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i3.5mm Maxiliary Input Jack3.5mm Min-Jack for VGAVGA (# of Ports)1 x VGA, D-sub 15 pin3.5mm Hadphone Jack (Output)3.5mm Min-Jack Audio OutSupported VGA SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480iMechanical FeaturesChasics ColorsBlackBlackTiltBackward; 15" Forward; 5"Bezel Width0.46"Neck / Stand DetachableYesVESA Mount Scree Wize (mm)75m x 75mmVESA Mount Scree Wize (mm)4 x 10mmNeck Scree Wize (mm)4 x 10mm (2pcs)Montor Neck Height (inches)3.15"Security LockDimensionDimension (inches, W x H x D)18.01" x 10.43" x 1.32"Vibhout Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Vibhout Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"<	Picture Presets	Standard, User, Movie, Eco, FPS, RTS
Type of SyncAdaptive SyncBlue Light ShiftAvailableAuto Dynamic Contrast ModeAvailableAuto Dynamic Contrast ModeAdjustableAuto FeaturesSpeakersSpeakers2 x 2W/4QInputs Samp; OutputsInputs Samp; OutputsHDMI (# of Ports & Version)1 x HDMI, 1.3 versionSupported HDMI SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60j, 720p,576p,576i,480p,480i3.5mm Aurillary Input Jack3.5mm Mini-Jack for VGAVGA (# of Ports)1 x VGA, D-sub 15 pin3.5mm Aurillary Input Jack3.5mm Mini-Jack Audio OutSupported VGA SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60j, 720p,576p,576i,480p,480iMechanical FeaturesChassis ColorsBlackBlackTiltBackward: 15° Forward: 5°Bezel Width0.46"Neck / Stand DetachableYesVESA Mount Pattern (nm)75mm x 75mmVESA Mount Pattern (nm)75mm x 75mmNeck Screw Size & Quantity (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensionDillo * x 10.43" x 1.32"Carton Box Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)3.74 ibs.Gross Weight With Stand (ltos)3.74 ibs.Net Weight with Stand (ltos)3.74 ibs.Gross Weight (ltos)6.49 ibs.PowerYep NameTypeAdapter 12V, 2A	Game Presets	FPS and RTS
Blue Light ShiftAvailableAuto Dynamic Contrast ModeAvailableGammaAdjustableAutio FeaturesSpeakers2 x 2W/4ΩInputs Samp; OutputsHDMI (# of Ports & Version)1 x HDMI, 1.3 versionSupported HDMI SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60p, 720p,576p,576(,480p,480i3.5mm Auxiliary Input Jack3.5mm Mini-Jack for VGAVGA (# of Ports)1 x VGA, D-sub 15 pin3.5mm Hadphone Jack (Output)3.5mm Mini-Jack Audio OutSupported VGA SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60j, 720p,576p,576(,480p,480iMechanical FeaturesChassis ColorsBlackTiltBackward: 15° Forward: 5°Bezel Width0.46°Neck / Stand DetachableYesVESA Mount Serew Size (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mmNeck Stand DetachableYesVESA Mount Stand (Inches, W x H x D)18.01" x 13.58" x 7.02"With Stand (Inches, W x H x D)18.01" x 13.58" x 7.02"With Stand (Inches, W x H x D)18.01" x 13.58" x 7.02"With Stand (Inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 13.58" x 7.02"Weight with Stand (Ibs)4.29 lbs.Net Weight with Stand (Ibs)3.74 lbs.Gross Weight (lbs)3.74 lbs.Gross Weight	OSD Supported Languages	English (Default), French, Spanish , Chinese
Auto Dynamic Contrast ModeAvailableGammaAdjustableAutio Features2 x 2W/4QInputs Samp: OutputsInputs Samp: OutputsFIDMI (# of Ports & Version)1 x HDMI, 1.3 versionSupported HDMI SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/601, 720p,576p,576i,480p,48013.5mm Auxiliary Input Jack3 Smm Mini-Jack for VGAVGA (# of Ports)1 x VGA, D-sub 15 pin3.5mm Headphone Jack (Output)3.5mm Mini-Jack Audio OutSupported KGA SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/601, 720p,576p,576i,480p,4801Mechanical FeaturesEChasis ColorsBlackTiltBackward: 15" Forward: 5"Bezel Width0.46"Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Sterew Size (mm)M4 x 10mmNeck Srew Size & Quantity (mm)M4 x 10mmNeck Sterew Size & Quantity (mm)18.01" x 10.3*8" x 7.02"With Stand (Inches, W x H x D)18.01" x 10.3* x 1.32"Carton Box Dimension (W x DElliptical, D1 = 7.02", D2=10.17"(Inches)3.74 lbs.Veright with Stand (Inches, M x H x D)3.74 lbs.Net Weight with Stand (Inches)3.74 lbs.Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(Inches)3.74 lbs.Veright with Stand (Ibs)3.74 lbs.ForewForewYangha Mathage Ma	Type of Sync	Adaptive Sync
GammaAdjustableAudio FeaturesSpeakers2 x 2W/4ΩInputs & OutputsHDMI (# of Ports & Version)1 x HDM1, 1.3 versionSupported HDMI SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i3.5mm Autilary Input Jack3.5mm Mini-Jack for VGAVGA (# of Ports)1 x VGA, D-sub 15 pin3.5mm Autilary Input Jack3.5mm Mini-Jack Audio OutSupported VGA SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480iMechanical FeaturesVersionChassis ColorsBlackBezel Width0.46*Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Pattern (mm)75mm x 75mmVESA Mount Screw Size (mm)M4 x 10mmMeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15*SecuritySecurity LockDimensions18.01* x 13.58* x 7.02*Withbut Stand (Inches, W x H x D)18.01* x 13.58* x 7.02*Vinches, WH x D)19.7* x 12.8* x 4.06*Stand Separation Dimension W x D (inches)Elliptical, D1 = 7.02*, D2=10.17*Weight with Stand (lbs)4.29 lbs.Net Weight with Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeTypeAdapter 12V, 2A	Blue Light Shift	Available
Audio Features Speakers 2 x 2W/4Q Inputs & Outputs HDMI (# of Ports & Version) 1 x HDMI. 1.3 version Supported HDMI Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i 3.5mm Auxiliary Input Jack 3.5mm Mini-Jack for VGA VGA (# of Ports) 1 x VCA, D-sub 15 pin 3.5mm Headphone Jack (Output) 3.5mm Mini-Jack Audio Out Supported VGA Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mochanical Foatures Chassis Colors Backward: 15° Forward: 5° Beackward: 15° Forward: 5° Bezel Width 0.46° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 10mm Neck Screw Size (mmin) M4 x 10mm Neck Screw Size (mmin) M4 x 10mm Neck Screw Size (mmin) M4 x 10mm Security Security Lock Dimensions 18.01" x 13.58" x 7.02" Without Stand (inches, W x H x D) 18.01" x 10.43" x 1.32"	Auto Dynamic Contrast Mode	Available
Speakers 2 x 2W/4Ω Inputs & Amp; Outputs HDMI (# of Ports & Version) 1 x HDMI, 1.3 version Supported HDMI Signals Up to 1600 x 900 (@ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i 3.5mm Auxiliary Input Jack 3.5mm Mini-Jack for VGA VGA (# of Ports) 1 x VGA, D-sub 15 pin 3.5mm Headphone Jack (Output) 3.5mm Mini-Jack Audio Out Supported VGA Signals Up to 1600 x 900 (@ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mechanical Features E Chassis Colors Black Tilt Backward: 15° Forward: 5° Bezel Width 0.46° VESA Mount Pattern (mm) 75mm X75mm VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 10mm Neck Screw Size & Quantity (mm) M4 x 10mm (2pcs) Monitor Neck Height (inches) 3.15" Security Security Lock Dimensions E With Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Without Stand (inches, W x H x D) 18.01" x 10.43" x 1.32"	Gamma	Adjustable
Inputs & Amp; Outputs HDMI (# of Ports & Version) 1 x HDMI, 1.3 version Supported HDMI Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i 3.5mm Auxiliary Input Jack 3.5mm Mini-Jack for VGA VGA (# of Ports) 1 x VGA, D-sub 15 pin 3.5mm Headphone Jack (Output) 3.5mm Mini-Jack Audio Out Supported VGA Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Machanical Features Chassis Colors Black Tilt Backward: 15° Forward: 5° Bezel Width 0.46" Ves VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size & Quantity (mm) M4 x 10mm Neck / Stand Detachable Yes VESA Mount Screw Size & Quantity (mm) M4 x 10mm (2pcs) Monitor Neck Height (inches) 3.15" Security Security Lock Dimensions Elliptical, D1 = 7.02", D2=10.17" Without Stand (Inches, W x H x D) 18.01" x 13.58" x 7.02" With Vith Stand (Ibs) 4.29 lbs. Net Weight with Stand (Ibs) 3.74 lbs. Gross Weight (lbs)	Audio Features	
HDMI (# of Ports & Version) 1 x HDMI, 1.3 version Supported HDMI Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i 3.5mm Auxiliary Input Jack 3.5mm Mini-Jack for VGA VGA (# of Ports) 1 x VGA, D-sub 15 pin 3.5mm Headphone Jack (Output) 3.5mm Mini-Jack Audio Out Supported VGA Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mechanical Features Chassis Colors Tilt Backward: 15" Forward: 5" Bezel Width 0.46" Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 10mm Neck Screw Size & Quantity (mm) M4 x 10mm (2pcs) Monitor Neck Height (inches) 3.15" Security Lock Dimensions With Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" With Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Without Stand (inches, W x H x D) 18.01" x 1.32" Carton Box Dimension (inches, W x H x D) 18.01" x 1.0.43" x 1.32" Carton Box Dimension (inches, W x H x D) 19.70", D2=10.17" (inc	Speakers	2 x 2W/4Ω
Supported HDMI Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i 3.5mm Auxiliary Input Jack 3.5mm Mini-Jack for VGA VGA (# of Ports) 1 x VGA, D-sub 15 pin 3.5mm Headphone Jack (Output) 3.5mm Mini-Jack Audio Out Supported VGA Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mechanical Features Editors Chassis Colors Black Tilt Backward: 15" Forward: 5" Bezel Width 0.46" Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 10mm Neck / Stand Leipht (inches) 3.15" Security Security Lock Dimensions Veith Stand (inches, W x H x D) With Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" With Stand (inches, W x H x D) 18.01" x 10.43" x 1.32" Carton Box Dimension (inches, W x H x D) 18.01" x 10.43" x 1.32" Carton Box Dimension (inches, W x H x D) Elliptical, D1 = 7.02", D2=10.17" Without Stand (lbs) 4.29 lbs. Net Weight without Stand (lbs) 3.74	Inputs & Outputs	
Supported HDMI Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i 3.5mm Auxiliary Input Jack 3.5mm Mini-Jack for VGA VGA (# of Ports) 1 x VGA, D-sub 15 pin 3.5mm Headphone Jack (Output) 3.5mm Mini-Jack Audio Out Supported VGA Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mechanical Features Editors Chassis Colors Black Tilt Backward: 15" Forward: 5" Bezel Width 0.46" Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 10mm Neck / Stand Leipht (inches) 3.15" Security Security Lock Dimensions Veith Stand (inches, W x H x D) With Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" With Stand (inches, W x H x D) 18.01" x 10.43" x 1.32" Carton Box Dimension (inches, W x H x D) 18.01" x 10.43" x 1.32" Carton Box Dimension (inches, W x H x D) Elliptical, D1 = 7.02", D2=10.17" Without Stand (lbs) 4.29 lbs. Net Weight without Stand (lbs) 3.74		1 x HDMI, 1.3 version
VGA (# of Ports)1 x VGA, D-sub 15 pin3.5mm Headphone Jack (Output)3.5mm Mini-Jack Audio OutSupported VGA SignalsUp to 1600 x 900 @ 75Hz; 1080/60i, 720p,576p,576i,480p,480iMechanical FeaturesChassis ColorsBlackTiltBackward: 15° Forward: 5°Bezel Width0.46°Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Pattern (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensions18.01" x 13.58" x 7.02"Without Stand (inches, W x H x D)18.01" x 13.58" x 4.06"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)4.29 lbs.Net Weight without Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)5.49 lbs.Net Weight without Stand (lbs)4.91 lbs.TypeAdapter 12V, 2A	Supported HDMI Signals	Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
3.5mm Headphone Jack (Output)3.5mm Mini-Jack Audio OutSupported VGA SignalsUp to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480iMechanical FeaturesChassis ColorsBlackTiltBackward: 15° Fonward: 5°Bezel Width0.46"Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Screw Size (mm)M4 x 10mmNeck K Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensions18.01" x 13.58" x 7.02"Without Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (inches, W x H x D)18.01" x 12.8" x 4.06"Stand Separation Dimension (inches, W x H x D)Elliptical, D1 = 7.02", D2=10.17"VeightNet Weight without Stand (lbs)A.29 lbs.3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeTypeAdapter 12V, 2A	3.5mm Auxiliary Input Jack	3.5mm Mini-Jack for VGA
Supported VGA Signals Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mechanical Features Endet Chassis Colors Black Tilt Backward: 15° Forward: 5° Bezel Width 0.46" Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 10mm Neck Screw Size & Quantity (mm) M4 x 10mm (2pcs) Monitor Neck Height (inches) 3.15" Security Security Lock Dimensions Is.01" x 13.58" x 7.02" With Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Without Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Without Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Without Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Without Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Without Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Without Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Weight K Elliptical, D1 = 7.02", D2=10.17" (inches) 3.74 lbs. <	VGA (# of Ports)	1 x VGA, D-sub 15 pin
Mechanical FeaturesChassis ColorsBlackTiltBackward: 15° Forward: 5°Bezel Width0.46"Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Screw Size (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensions18.01" x 13.58" x 7.02"With Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (inches, W x H x D)18.01" x 12.8" x 4.06"Stand Separation Dimension (W x D (inches)Elliptical, D1 = 7.02", D2=10.17"WeightNet Weight with Stand (lbs)A.29 lbs.3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeTypeAdapter 12V, 2A	3.5mm Headphone Jack (Output)	3.5mm Mini-Jack Audio Out
Chassis ColorsBlackTiltBackward: 15° Forward: 5°Bezel Width0.46"Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Screw Size (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensions18.01" x 13.58" x 7.02"With Stand (inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)18.01" x 2.8" x 4.06"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)4.29 lbs.Net Weight with Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeTypeAdapter 12V, 2A	Supported VGA Signals	Up to 1600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
TiltBackward: 15° Forward: 5°Bezel Width0.46"Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Screw Size (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensionsWith Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)18.01" x 10.43" x 1.32"WeightElliptical, D1 = 7.02", D2=10.17"(inches)X.29 lbs.Net Weight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeAdapter 12V, 2A	Mechanical Features	
Bezel Width0.46"Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Screw Size (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensionsWith Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)18.01" x 12.8" x 4.06"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)4.29 lbs.Net Weight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeTypeAdapter 12V, 2A	Chassis Colors	Black
Neck / Stand DetachableYesVESA Mount Pattern (mm)75mm x 75mmVESA Mount Screw Size (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensionsWith Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)18.01" x 12.8" x 4.06"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)4.29 lbs.Net Weight with Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerFowerTypeAdapter 12V, 2A	Tilt	Backward: 15° Forward: 5°
VESA Mount Pattern (mm)75mm x 75mmVESA Mount Screw Size (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensionsWith Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)19.76" x 12.8" x 4.06"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)VeightWeight.Net Weight without Stand (lbs)4.29 lbs.Net Weight (lbs)6.49 lbs.Power.TypeAdapter 12V, 2A	Bezel Width	0.46"
VESA Mount Screw Size (mm)M4 x 10mmNeck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensionsWith Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)19.76" x 12.8" x 4.06"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)WeightWeight	Neck / Stand Detachable	Yes
Neck Screw Size & Quantity (mm)M4 x 10mm (2pcs)Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensionsWith Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)18.01" x 10.43" x 1.32"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)WeightWeight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeTypeAdapter 12V, 2A	VESA Mount Pattern (mm)	75mm x 75mm
Monitor Neck Height (inches)3.15"SecuritySecurity LockDimensionsWith Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)19.76" x 12.8" x 4.06"Elliptical, D1 = 7.02", D2=10.17"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)VeightWeight.Net Weight with Stand (Ibs)4.29 lbs.Net Weight without Stand (Ibs)3.74 lbs.Gross Weight (Ibs)6.49 lbs.PowerTypeAdapter 12V, 2A	VESA Mount Screw Size (mm)	M4 x 10mm
SecuritySecurity LockDimensionsWith Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)19.76" x 12.8" x 4.06"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)VeightNet Weight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeAdapter 12V, 2A	Neck Screw Size & Quantity (mm)	M4 x 10mm (2pcs)
Dimensions With Stand (inches, W x H x D) 18.01" x 13.58" x 7.02" Without Stand (Inches, W x H x D) 18.01" x 10.43" x 1.32" Carton Box Dimension (inches, W x H x D)19.76" x 12.8" x 4.06" Stand Separation Dimension W x D Elliptical, D1 = 7.02", D2=10.17" (inches) Elliptical, D1 = 7.02", D2=10.17" Weight 4.29 lbs. Net Weight with Stand (lbs) 4.29 lbs. Net Weight without Stand (lbs) 3.74 lbs. Gross Weight (lbs) 6.49 lbs. Power Type Adapter 12V, 2A	Monitor Neck Height (inches)	3.15"
With Stand (inches, W x H x D)18.01" x 13.58" x 7.02"Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)19.76" x 12.8" x 4.06"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)VeightWeight4.29 lbs.Net Weight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeAdapter 12V, 2A	Security	Security Lock
Without Stand (Inches, W x H x D)18.01" x 10.43" x 1.32"Carton Box Dimension (inches, W x H x D)19.76" x 12.8" x 4.06"Stand Separation Dimension W x DElliptical, D1 = 7.02", D2=10.17"(inches)WeightWeight4.29 lbs.Net Weight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeAdapter 12V, 2A	Dimensions	
Carton Box Dimension (inches, W x H x D)19.76" x 12.8" x 4.06"Stand Separation Dimension W x D (inches)Elliptical, D1 = 7.02", D2=10.17"Weight4.29 lbs.Net Weight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeAdapter 12V, 2A	With Stand (inches, $W \times H \times D$)	18.01" × 13.58" × 7.02"
Stand Separation Dimension W x D (inches)Elliptical, D1 = 7.02", D2=10.17"WeightElliptical, D1 = 7.02", D2=10.17"Weight4.29 lbs.Net Weight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeTypeAdapter 12V, 2A	Without Stand (Inches, $W \times H \times D$)	18.01" x 10.43" x 1.32"
(inches)Image: Sector Sect	Carton Box Dimension (inches, W x H x D	0)19.76" x 12.8" x 4.06"
WeightNet Weight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeAdapter 12V, 2A	Stand Separation Dimension W x D	Elliptical, $D1 = 7.02$ ", $D2=10.17$ "
Net Weight with Stand (lbs)4.29 lbs.Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerTypeAdapter 12V, 2A	(inches)	
Net Weight without Stand (lbs)3.74 lbs.Gross Weight (lbs)6.49 lbs.PowerAdapter 12V, 2A	Weight	
Gross Weight (lbs) 6.49 lbs. Power Type Adapter 12V, 2A	Net Weight with Stand (lbs)	4.29 lbs.
Power Type Adapter 12V, 2A	Net Weight without Stand (lbs)	3.74 lbs.
Type Adapter 12V, 2A	Gross Weight (lbs)	6.49 lbs.
	Power	
Power Range (V, A, Hz) 100 – 240 VAC, 50/60 Hz	Туре	Adapter 12V, 2A
	Power Range (V, A, Hz)	100 – 240 VAC, 50/60 Hz

SCEPTRE®	
Power Consumption (Typical)	18.14W
Maximum	20.45W
Standby	<0.5W
Sleep	<0.11W
Off	<0.08W
Regulations / Certifications	
Regulations	RoHS, cTUVus, FCC
Certifications	ISTA6A, HDMI
Warranty	
Limited Parts and Labor	One Year
What's in the Box?	
Power Cable	AC Power Adapter x 1
Display Cable	HDMI Cable x 1
Accessories	User Manual, Warranty Card, Neck Screws x 2, Screwdriver x 1





LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.



75Hz Refresh Rate

With 75Hz refresh rate, images change faster and smoother than the standard, reducing screen tearing



Fast Response Time

Fast response times reduce ghosting & blurring while transitioning pixels, always keeping the enemy & terrain precisely in focus during chaotic moments.

TEARING DESCRIPTION

ADAPTIVE SYNC ON

Adaptive Sync

ADAPTIVE SYNC OFF

Adaptive Sync is a technology that closes the gap between the graphics card's and the monitor's refresh rates, eliminating image tearing and stuttering in the process.



Built in Speakers

Perfectly suited to work & gaming settings, built-in speakers deliver robust & smooth audio while saving space on your desk.



Multiple Ports

The HDMI, and VGA ports accelerate refresh rate up to 75Hz, providing the visual edge you need to defeat the competition during all of your gaming exploits.



Key Features

SECURITY LOCK COMPATIBLE



Security Lock

The monitor has a security slot, allowing you to securely fasten your monitor in place, effectively preventing theft. *Security Lock not included.



VESA Wall Mountable

The VESA wall mount pattern gives you the freedom to select the optimum viewing position for your monitor, eliminate cable clutter, & save valuable space for your gaming & work station. -5° 15°

Tiltable Display

A display that tilts 15° backward and 5° forward allows you to find a sweet spot that bridges clarity and comfort.



Blue Light Shift

Blue Light Shift reduces blue light, allowing you to comfortably work, watch, or play applications without straining your eyes.



Anti-Flicker

Provides a crisper picture by preventing the backlight from flickering periodically.



FPS-RTS Game Modes

FPS and RTS are Sceptre's custom set display settings built for an enhanced gaming experience. FPS (First Person Shooter), RTS (Real-Time Strategy).





Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.



30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.